X-JET NOZZLE

Long range External Chemical Injection

FEATURES

- Two versions to choose from.
 - o Original X-Jet with fixed long and close range spray patterns
 - X-Jet M5 with Adjustable spray pattern from 5 to 60 Degree spray pattern.
- Apply soap & rinse with the same nozzle
- Projects chemicals up to 40ft or more depending on your machine
- NO chemicals run through the pump, hose, reels, gun, lance, or quick connects.
- Color coded proportioners to apply chemicals at different ratios


SPECIFICATIONS



X-Jet M5



Style	The Original X-Jet (Fixed)				X-Jet M5 (Adjustable)			
Model	XJET-07K	XJET-09K	XJET-13K	XJET-16K	XJETM5-07K	XJETM5-09K	XJETM5-13K	XJETM5-16K
Operating	2000-3000	2000-3000	3000-4000	3000-3500	2000-3000	2000-3000	3000-4000	3000-3500
Pressure	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI
GPM Flow	2 - 2.5	3 - 3.5	4 - 6	6.5 - 8	2 - 2.5	2.5 - 3.5	4 - 6	6.5 - 8
Maximum	190° F			190° F				
Temperature								
Port Sizes	Inlet ¼" Quick Connect Plug			Inlet ¼" Quick Connect Plug				
	Chemical Port 1/8 MPT x 3/8" Hose Barb			Chemical Port 1/8 MPT x 3/8" Hose Barb				
Dimensions	3.78" x .87" x 2.0"			5.38" x 1.25" x 2.38"				
Weight	4.8 oz.				6.4 oz.			



Item	Part	Description	
1	N/A	X-Jet body-Not sold separately	
*2	OR <u>(X)</u>	Orifice (X is selected size 7,9,13, 16 (See model number in chart above) Larger sizes available	
3	XSPR	Spring	
4	XMP	1/4" Quick Connect Plug	
5	XSHB	Nozzle Hose Barb	
6	XCRMN	Close Range Meg Nozzle	
7	XCRNRV	Close Range Nozzle Vane	
8	XCRNA	Close Range Nozzle Adapter	
**9	XM5RVN	Variable Nozzle	
31	XCRNAS	Close Range Nozzle Assembly (Items 10-14)	

^{*}Special Order sizes available for machines larger than 8GPM #20 orifice recommended for 10 GPM

^{**9-} Replaceable; However, be advised variable nozzle is machined on to X-Jet body at factory for proper vertical fan orientation. With replacement by hand, orientation of spray pattern cannot be guaranteed.

Item	Part	Description	Item	Part	Description
10	ХЈН	3/8" Hose per ft	20	XPP-BLUE	Blue Proportioner
11	XSPDC	Clamps (2)	21	XPP-TAN(MED)	Tan Proportioner
12	XSOV	Shut Off Valve	22	XPP-GREEN	Green Proportioner
13	XBSHB	Hose Assembly Barb	23	XPP-ORANGE	Orange Proportioner
14	XBS	Ball Strainer Screen	24	XPP-BROWN	Brown Proportioner
15	XPP-GREY	Grey Proportioner	25	XPP-YELLOW	Yellow Proportioner
16	XPP-BLACK	Black Proportioner	26	XPP-AQUA	Aqua Proportioner
17	XPP-BEIGE	Beige Proportioner	27	XPP-PURPLE	Purple Proportioner
18	XPP-RED	Red Proportioner	28	XPP-PINK	Pink Proportioner
19	XPP-WHITE	White Proportioner	29	CLEAR	CLEAR NOT USED

		32
11		
13.	14	
	13.	14

Kit	XJET-XX	Original X-Jet Kit (Items 1-8, 30 & 32) XX is selected orifice size 7,9,13 or 16
Kit	XJETM5-XX	M5 X-Jet Kit (Items 1-5, 9, 30, & 32) XX is selected orifice size 7,9,13 or 16
30	XPP-PACK	Proportioner Pack (Items 15-29)
31	XCRNAS	Close Range Nozzle Assembly (Items 6-8)
32	XHA	Hose Assembly (Items 10-14)



INSTALLATION

Read the instructions & warnings included with your X-Jet in its entirety before installation. Determine the X-Jet model you need based on the operating pressure and GPM of your machine. Connect the X-Jet to the gun or lance via a ¼" quick connect coupler (not included). Make sure it is properly connected before turning the pressure on. Always aim the nozzle away from all surfaces and people when first turning the pressure on to ensure the X-Jet is securely connected. Never aim the nozzle towards any person or animal in any circumstance. Always use the proper personal protective equipment when using the X-Jet Nozzle. Under no circumstances should the pressure of the pressure washer in use exceed the maximum rated pressure of any component.

TROUBLESHOOTING

Problem	Cause	Solution	
X-Jet will not draw chemical	Shut off valve in hose has failed	Replace shut off valve	
	Shut off valve is closed	Twist valve to open position	
	Incorrect orifice size	Replace orifice with correct orifice size	
	Crack in chemical hose	Replace chemical hose	
	Debris is in barb or hose	Clean debris out of hose or barb	
	Pressure Washer is not working properly	Verify proper operating pressure & GPM	
Water is shooting out hose barb	Missing or Incorrect orifice size	Install or replace with correct size	
	Debris is in orifice	Clean debris out of orifice	
Water stream is too misty	Incorrect orifice size	Replace orifice with correct orifice size	
	Pressure Washer is not working properly	Verify proper operating pressure & GPM	
Water stream does not shoot far	Close range nozzle is attached to original X-Jet	Remove close range nozzle	
	Incorrect Orifice Size	Replace orifice with correct orifice size	
	Adjustable M5 nozzle is in closed position	Twist the adjustable nozzle to open	
	Pressure Washer is not working properly	Verify proper operating pressure & GPM	